

D-2000P

Styrofoam adhesive

**DAEHEUNG CHEMICAL**

D-2000P is a vinyl acetate polymer base adhesive which is excellent in initial bonding strength. This adhesive is used to bond the wood, paper, fiber glass and rock wood, etc.

1. Uses

- Mutual bonding of wood paper, fiber glass and rock wood.
- Bonding for insulation to metal, concrete, wood etc.
- Bonding for polystyrene foam to concrete and wood, stile to concrete, metal etc.

2. Characteristics

- Excellent in initial bonding strength.
- Dry film in good resistance to light and water.
- Good transparency and insulation properties.
- Rapid drying speed.

3. Physical properties

Properties	Value
Main component	Vinyl acetate
Color	Pink & viscous liquid
Solid contents	33.5±1 % (at 105±5°C x 3hr)
Viscosity	2,500±100 cps (at 25°C, RION VT-04 #1)
Solvent	Alcohol
Shelf life	9months in unbroken package under dry and cool condition

4. How to use

- Remove all dirt, grease, water and rust from the bonding surface before applying.
- Coating adequate amount of adhesive by brush or roller and then joint them.
- Press with hand roller or other mechanical system.
 - Applying amount : 120~200 g/m²
 - Work tools : Brush, Hera, Spatula, Roll etc.
 - Press : Hand roller press etc.
 - Curing time : Over 24 hr

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place
- Ventilation the room well because of containing solvent.
- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- Keep out of reach of children.
- Close the cap tightly after using it.
- Store at room temperature.
- Don't use except for the original purpose.

6. Packaging

- 800g C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-668-1424

Facsimile +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL