# D-3361

**PVC** adhesive



D-3361 is a vinyl chloride copolymer base adhesive, which is excellent in initial bonding strength. This adhesive is used to bond the soft PVC, PVC board, PVC pipe and plastics etc.

#### 1. Uses

- Bonding for rigid and soft PVC, PVC board.
- Bonding for PVC pipe and plastic materials, etc.

#### 2. Characteristics

- Excellent in initial bonding strength.
- Quick drying speed and fast set.
- Excellent in water and alkali resistance.
- Good workability.

#### 3. Physical properties

Properties	Value
Main component	Vinyl chloride copolymer
Color	Clear & viscous liquid
Solid contents	23±1 % (at 105±5℃ × 3hr)
Viscosity	440~460 cps (at 20℃, RION VT-04 #1)
Solvents	MEK & Toluene solvents
Open time	2~5 min (at 20 ℃)
Shelf life	9months in unbroken package under dry and cool condition

#### 4. How to use

- Remover all dirt, grease, water and rust from the surface before applying.
- Coat adequate amount of adhesive, and joint them.
- Press with hand, roller or other mechanical system.
  - Applying amount: 120~200 g/m<sup>2</sup>
  - Work tools: Brush, Hera, Spatula, Roll etc.
  - Press pressure: 5~10 kg/cm<sup>2</sup>
  - Curing time: Above 24 hr

## 5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Keep out of reach of children.
- Keep it away from the fire.
- Ventilation the room well because of containing solvent.
- Close the cap tightly after using it
- Don't use except for the original purpose.

# 6. Packaging

- 30ml Tube
- 1kg, 3kg, 15kg C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

## DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggido, Korea

**Telephone** +82-2-554-8211, +82-31-668-1424 **Facsimile** +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr

