DF-570

Acryl adhesive



DF-570 is an acrylic resin adhesive for the use of bottom which is great in PVC carpet & tile's adhesive property and cold resistance, heat resistance. This adhesive has a LONG TACK as all round adhesive, and so it is excellent in working construction.

1. Uses

- Adhesive for the use of bottom a PVC carpet & tile (deco tile, rex tile, sense tile, deluxe tile etc.)
- For indoor and outdoor use
- Especially in the interior floors are environmentally friendly are required

2. Characteristics

- Long tack, this adhesive is possible for one side anointment.
- An excellent in initial bonding strength property.
- Reconstruction is convenient because this adhesive is aqueous adhesive.
- Cold-resistant adhesive property is comparatively satisfactory. (until 20 ℃)

3. Physical properties

Properties	Value
Main component	Acrylic resin emulsion
Color	Pale yellow
Solid contents	70±2 % (at 105±5℃ x 3hr)
Viscosity	13,000 ~ 17,000 cps (at 20 ℃)
Specific gravity	1.2~1.4
Open time	10~120 min
Using time	After 24 hr
Application temperature	5 ~ 30 ℃
Application quantity	300±50 g/m²
Shelf life	9 months in unbroken package under dry and cool condition

4. How to use

- Remover all dirt, grease, water and rust from the surface before applying.
- Spread thinly the adhesive over one of the surfaces to be bonded by using applicator.
- After application, wait for a moment (10 ~ 60 min) and bond.
- Press with hand enough.

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place. (5~25 ℃)
- The brush and other tools for spreading the adhesive, the stain parts and hands, etc, should be cleaned by wiping or washing with water.
- Keep out of reach of children.
- Close the cap tightly after using it
- Don't use except for the original purpose.

6. Packaging

• 4kg, 10kg PE C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si,

Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-668-1424 **Facsimile** +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL