DH-7700 Paint film waterproof agent (One-component)



DAEHEUNG CHEMICAL

DH-7700 is pure acrylic emulsion. It forms elastic and tough water proofing membrane mixing with inorganic material. It features excellent weather-resistance, strong adhesiveness and elasticity also. It is environmental-friendly agent that doesn't cause any environmental contamination or poison.

1. Uses

- Elastic waterproofing agent.
- Floor finishing adhesive

2. Characteristics

- Good elastic membrane waterproofing agent.
- Good flow characteristic and workability.
- Non toxic and odorless.

3. Physical properties

Properties	Value
Main component	Pure Acrylic Copolymer
Appearance	Milky white emulsion
Solid contents	60±2 % (at 105±5 ℃, 3hr)
Viscosity	7,000~13,000 cps (at 25℃)
Specific gravity	1.05 g/cm³ (at 20℃)
рН	6.0±0.5

4. How to use

- Dilute cement with water, and mix the DH-7700.(Use hand mixer or stir with a rod.)
- Coated evenly using a brush, roller or the like.
- The applied thickness is suitably in the 1.5 ~ 2.5mm.
- After the second coating(at least 12 hours after complete drying) waterproof construction, please tertiary waterproof coating.

5. Caution

- Avoid direct rays of the sun and keep in cool(5~25 ℃) and dry place.
- Keep at least 5 °C to avoid freezing.
- Please use After taking roll up the film before use, it may cause the coating to dry on the surface of the adhesive during prolonged storage.
- After use, please keep the remaining adhesive seal.
- If the use of glue spills, please wipe with a damp cloth.Don't carry out the construction if temperature is 5°C and below or humidity is 85% and above.

6. Packaging unit

• 18kg PE

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si, Gyeonggi-

do, Korea

Telephone +82-2-554-8211, +82-31-668-1424

Facsimile +82-2-554-8215, +82-31-668-1425

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL