

NO 2-4



DAEHEUNG CHEMICAL

Gasket

NO 2-4 is a semi-drying liquid gasket that uses synthetic rubber as the main ingredients. Especially, has a excellent resistance to heat, oil, gasoline.

1. Uses

- Flange or screw section
- Automotive, agricultural equipment, ships and general machinery etc.

2. Characteristics

- Excellent resistance to heat, oil, gasoline.
- Pressure resistance at high temperature is good.
- Superior vibration resistance and impact resistance.

3. Physical properties

Properties	Value
Main component	Synthetic rubber
Color	Light brown viscosity liquid
Solid contents	44~46 % (at 105±5℃, 3hr)
Viscosity	22,000~24,000 cps (at 20℃, RION VT-04 #2)
Open time	5~30 min (at 20℃)
Dilution solvent	Ketone
Application temperature	-40 ~ 150 ℃
Shelf life	9months in unbroken package under dry and cool condition

4. How to use

- Remove all dirt, grease, water and rust from the bonding surface before applying
- Please assembled in a dry state.(dry within Open time)
- Please be sure to stir before using, be sure to have sealed after use, please keep in cool dark place management.

5. Caution

- Avoid direct rays of the sun and keep in cool and dry place.
- Use with adequate ventilation and avoid prolonged breathing of vapors.
- Don't use except for the original purpose.
- Keep out of reach of children.

6. Packaging

- 1kg C/N

Please contact us for further information or see Material Safety Data Sheet (MSDS) for this product.

DAEHEUNG CHEMICAL CO., LTD.

68, Sandan-ro 64beon-gil, Pyeongtaek-si, Gyeonggi-do, Korea

Telephone +82-2-554-8211, +82-31-663-5251

Facsimile +82-2-554-8215, +82-31-664-3361

Website www.dhcbond.co.kr



DAEHEUNG CHEMICAL